


(7) ^{ハイアム} ^{ディナ} **HiAm & DIN**アンカーケーブル



1) 亜鉛めっき鋼線 7 mm 使用

(SPWC241の断面の例)

鋼線本数 本	断 面 積 mm ²	破断荷重 kN	鋼線外径 mm	被覆外径 mm	被 覆 厚 mm	鋼線質量 kg/m	ケーブル質量 ¹⁾ kg/m
(19)	731	1150	35.0	45	4.5	5.7	6.5
31	1,190	1870	44.0	55	5.0	9.3	10.4
37	1,420	2240	49.0	60	5.0	11.1	12.4
55	2,120	3320	57.5	70	5.5	16.6	18.2
(61)	2,350	3690	63.0	75	5.5	18.4	20.4
73	2,810	4410	68.0	80	5.5	22.0	24.1
85	3,270	5140	71.2	85	6.5	25.6	27.9
(91)	3,500	5500	77.0	90	6.0	27.4	30.1
109	4,190	6590	81.1	95	6.5	32.8	35.5
121	4,660	7310	84.9	100	7.0	36.4	39.4
(127)	4,890	7670	91.0	105	6.5	38.2	41.8
139	5,350	8400	92.2	105	6.0	41.8	44.9
151	5,810	9120	94.4	110	7.5	45.5	49.0
163	6,270	9850	98.8	115	7.5	49.1	53.0
187	7,200	11200	105.0	120	7.0	56.3	60.2
199	7,660	12000	108.0	125	8.0	59.9	64.3
(211)	8,120	12700	112.7	130	8.0	63.5	68.4
223	8,580	13500	116.3	135	9.0	67.1	72.5
241	9,270	14600	119.0	135	7.5	72.5	77.3
253	9,740	15300	121.6	140	8.5	76.2	81.6
(265)	10,200	16000	126.6	145	8.5	79.8	85.8
283	10,900	17100	129.0	150	10.0	85.2	91.6
295	11,400	17800	131.4	150	9.0	88.8	94.7
301	11,600	18200	133.0	155	10.5	90.6	97.5
313	12,000	18900	135.3	155	9.5	94.2	100.7
337	13,000	20400	140.6	160	9.0	101.0	107.7
349	13,400	21100	142.0	165	11.0	105.0	112.6
361	13,900	21800	144.9	165	9.5	109.0	116.1
367	14,100	22200	147.0	170	11.0	110.0	118.1
(379)	14,600	22900	149.1	170	10.0	114.0	121.7
397	15,300	24000	153.2	175	10.5	119.0	127.3
421	16,200	25400	155.2	180	12.0	127.0	135.8
451	17,400	27200	162.9	190	13.0	136.0	146.4
499	19,200	30100	168.5	195	12.5	150.0	160.1

注 1) ケーブルの質量には PE 被覆を含む。

2) () 印のケーブルの断面は六角形となる。